

PRODUCT-DETAILS

# ACH580-01-018A-4

## ACH580-01-018A-4 PN: 7.5 kW, IN: 17.0 A



### General Information

Global Commercial Alias	ACH580-01-018A-4
Product ID	3AXD50000038993
ABB Type Designation	ACH580-01-018A-4
EAN	6438177459484
Catalog Description	ACH580-01-018A-4 PN: 7.5 kW, IN: 17.0 A

Long Description	<p>ACH580 HVAC drive offering has all key features built-in to control fans, pumps and compressors, and more complex equipment like air-handling units and chillers, ensuring smooth, energy-efficient operation of your HVAC systems in normal and mission-critical situations. The built-in features significantly reduce installation time and the intuitive control panel with an HVAC-specific primary settings menu and help assistants makes startup, commissioning and operation easy. The optional Bluetooth® capability enables the commissioning and monitoring of the drive from a distance. The ACH580-01 comes in IP21 enclosure and can be installed on the wall as standard. Also, IP55 and flange mounting units are available.</p>
------------------	--

### Ordering

Country of Origin	Romania (RO) Finland (FI) China (CN)
Customs Tariff Number	85044086
Invoice Description	ACH580-01-018A-4 PN: 7.5 kW, IN: 17.0 A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

---

**Container Information**


---

Gross Volume	13.54 dm <sup>3</sup>
--------------	-----------------------

---



---

**Dimensions**


---

Product Net Weight	6.6 kg 14.551 lb
Product Net Depth / Length	228.50 mm 9.02 in
Product Net Height	473.00 mm 18.62 in
Product Net Width	125.00 mm 4.92 in
Package Level 1 Depth / Length	225.00 mm 8.858 in
Package Level 1 Height	370.00 mm 14.567 in
Package Level 1 Width	621.00 mm 24.449 in
Package Level 1 Units	1 carton

---



---

**Technical**


---

Number of Phases	3
Degree of Protection	IP21
Enclosure Type NEMA	Type1
Altitude	1000 m 95
Sound dB (A)	64 dB(A)
Multiple Battery Information	Lithium Coin, CR2032, 220 mAh, 3 V, 1 pc, 3 g
Frequency (f)	47 ... 63 Hz
Frame Size	R2
Input Voltage (U <sub>in</sub> )	380 ... 480 V
Mounting Type	Wall-mounted
Communication Protocol	BACNET CAN DeviceNet EtherNet/IP LON MODBUS Other Bus Systems PROFIBUS PROFINET IO TCP/IP
Number of Hardware Interfaces	Industrial Ethernet 0 Other 2 Parallel 2 PROFINET 0 RS-232 0 RS-422 0 RS-485 1 Serial TTY 0 USB 1
Includes	Control unit PC connection
Analog Inputs	2
Analog Outputs	2
Number of Digital In/Outputs	6/3
Output Current, Heavy- Duty Use (I <sub>HD</sub> )	12.6 A
Output Current, Light-	16.2 A

Overload Use ( $I_{LD}$ )	
Output Current, Normal Use ( $I_n$ )	17 A
Output Power, Heavy-Duty Use ( $P_{HD}$ )	5.5 kW
Output Power, Light-Overload Use ( $P_{LD}$ )	7.5 kW
Output Power, Normal Use ( $P_n$ )	7.5 kW
Apparent Power Output	12 kV·A
Efficiency Level	IE2
Standby Loss	15 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Efficiency	Relative Loss
0/25 %	91 W	87.2 %	0.8 %
0/50 %	114 W	91.4 %	1.0 %
0/100 %	189 W	92.7 %	1.6 %
50/25 %	96 W	93.1 %	0.8 %
50/50 %	124 W	95.3 %	1.1 %
50/100 %	210 W	96.0 %	1.8 %
90/50 %	134 W	97.1 %	1.1 %
90/100 %	240 W	97.4 %	2.0 %

Temperature Rating	Maximum 40 °C Minimum -15 °C
--------------------	---------------------------------

## Additional Information

Product Main Type	ACH580-01
Product Name	Frequency converter

## Classifications

ETIM 7	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

## Environmental

SCIP	4a4ed2db-43e7-4612-8e9c-3921e4acd08b Finland (FI)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

Drives → Low Voltage AC Drives → Industry-Specific Drives → Drives for HVAC → ACH580-01 - Wall-mounted drive for HVAC

