BMFW263/AC300 1/3



PRODUCT-DETAILS

## BMFW263/AC300 BMFW263/AC300 Residual Current Circuit Breaker AC Type, 2P, 63A, 300mA



General Information	
Extended Product Type	BMFW263/AC300
Product ID	1SYF602062R3630
EAN	8906176431520
Catalog Description	BMFW263/AC300 Residual Current Circuit Breaker AC Type, 2P, 63A, 300mA
Long Description	The RCCB BMFW263/AC300 assures protection to people and installations against fault current to earth. This product is manufactured according to IEC Standards for the markets where it is required.

Technical	
Electrical Endurance	10000 cycle
Mechanical Endurance	10000 cycle
Number of Poles	2P
Recommended Screw Driver	Pozidriv 2
Connecting Capacity	Flexible 35 mm²
	Flexible Solid;25 mm²

## Electrical

BMFW263/AC300 2/3

Rated Voltage (U <sub>r</sub> )	230 V
Rated Impulse Withstand	4 kV
Voltage (Ü <sub>imp</sub> )	
Input Voltage Type Rated Current (I <sub>n</sub> )	AC 63 A
Rated Frequency (f)	50 Hz
Material Compliance	
RoHS Information	No declaration needed
REACH Information	No data - If REACH inform is not yet available for a certain product
Conflict Minerals Reporting Template	9AKK108468A3363
(CMRT)	
WEEE Category	Product Not in WEEE Scope
Environmental	
Ambient Air Temperature	Operation -25 +55 °C
Degree of Protection	IP20
Dimensions	
Product Net Width	35 mm
Product Net Height	88 mm
Product Net Depth /	74.25 mm
Length Product Net Weight	0.159 kg
Ordering	
Ordering  Parkers I world Heite	h4t
Package Level 1 Units Package Level 1 Gross	
Weight	
Certificates and Declarations	
Declaration of Conformity - CE	9AKK108469A0983
Installation	
Instructions and Manuals	9AKK108469A0989
Popular Downloads	
Data Sheet, Technical Information	9AKK108469A4847
External Classifications and Standards	
ETIM 9 ETIM 10	EC000003 - Residual current circuit breaker (RCCB) EC000003 - Residual current circuit breaker (RCCB)

BMFW263/AC300 3/3

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Formula Din Rail → Residual Current Circuit Breakers, Formula Din Rail

