



PRODUCT-DETAILS

OVR T1-T2 12.5-275s C QS

OVR T1-T2 12.5-275s C QS Surge Protective Device



General Information	
Extended Product Type	OVR T1-T2 12.5-275s C QS
Product ID	2CTB815710R2600
EAN	3660308525031
Catalog Description	OVR T1-T2 12.5-275s C QS Surge Protective Device
Long Description	Surge protective devices SPD type 1- type 2 protect low-voltage consumer systems against lightning currents and surge voltages as they are tested as SPD type 1 and type 2 according to IEC 61643-11. The devices are compatible with the System pro M compact series. The SPD with "TS" are optionally equipped with a auxiliary contact. The variants with "reserve varistor" (s) offer additional protection for the system, as the SPD is not completely disconnected from the mains at the end of its service life, but with an additional smaller varistor still guarantees basic protection and the system thus until the surge arrester is replaced is still protected

Technical	
Type of Low Voltage Distribution System	TT TN-C TN-S
Suitable For	To protect the systems against the transient overvoltage (lightning)
Nominal AC Voltage of the System (U _o)	230 / 400 V
Maximum Continuous	(L-PE) 275 V

Operating Voltage (U _c)	(L-L) 275 V (L-N) 275 V (N-PE) - V
Temporary Overvoltage Test Value (U _T)	337 V
Discharge Current	Nominal 20 kA Maximum 80 kA
Impulse Current	I (imp, 10 / 350 µs) 12.5 kA I (total, 10 / 350 µs) - kA
Lightning Impulse Current	12.5 kA
Short Circuit Withstand I _{cc}	100 kA
Arrester Class	I II
Number of Protected Poles	1
Number of Poles	1P
Version	Plug-in
Product Type	QS
Options Provided	Replacement Cartridge
Preventive Maintenance Feature	Yes
Status Indicator	Yes
Fuse Size	1 modular spacing

Electrical

Voltage Protection Level (U _p)	(L-N) 1.4 kV (N-PE) - kV (L-PE) 1.4 kV
Power Loss	Total 37 mW

Material Compliance

RoHS Declaration	9AKK108466A4617
RoHS Information	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20230707
REACH Declaration	9AKK107492A1906
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20231212
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

Environmental

Degree of Protection	IP20
Maximum Operating Altitude Permissible	Without Derating 5000

Dimensions

Width in Number of Modular Spacings	1
Product Net Width	17.6 mm
Product Net Height	57 mm
Product Net Depth / Length	67 mm
Product Net Weight	0.1 kg

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	115 g
E-Number (Finland)	3217624
E-Number (Norway)	1623953

Certificates and Declarations

CQC Certificate	9AKK107680A1975
Declaration of Conformity - CE	9AKK108466A4617

Installation

Instructions and Manuals	2CTC431030M1701
Mounting Type	DIN-Rail

Popular Downloads

Data Sheet, Technical Information	No document needed
-----------------------------------	--------------------

External Classifications and Standards

ETIM 9	EC001457 - Combined arrester for power supply systems
ETIM 10	EC001457 - Combined arrester for power supply systems
UNSPSC	39121610
eClass	V11.0 : 27130808
Object Classification Code	141BCC
Standards	IEC 61643-11 / EN 61643-11

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Surge Protective Devices SPDs → Surge Protective Devices SPDs Accessories

